## AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

## LISTING OF CLAIMS:

## 1-14. (canceled)

- insert for a joint prosthesis, the insert comprising a metal shell and a polymer lining lining the inside space of said shell, a receptacle for a prosthetic head being formed in the lining, said shell presenting on its inside space means for preventing said lining being extracted from the shell and means for preventing the lining turning in the shell, wherein said means for preventing the lining being extracted comprise a stud disposed on an end wall of the posterior portion of the inside space of the shell, said stud having at least one groove or lip with which the lining interfits to lock the lining on the shell.
- 16. (previously presented) The insert according to claim 15, wherein said means for preventing extraction of said lining include at least one lip.
- 17. (previously presented) The insert according to claim 15, wherein said means for preventing said lining being extracted include at least one groove.

- 18. (previously presented) The insert according to claim 15, wherein said means for preventing the lining from turning comprise projections formed on the surface of the wall defining the inside space of the shell.
- 19. (previously presented) The insert according to claim 18, wherein said projections are ribs extending over all or a fraction of the height of the inside space of the shell.
- 20. (previously presented) The insert according to claim 15, wherein said means for preventing the lining from turning comprise depressions formed in the surface of the wall defining the inside space of the shell.
- 21. (previously presented) The insert according to claim 16, wherein said means for preventing the lining from turning comprise projections formed on the surface of the wall defining the inside space of the shell, and wherein projections are formed on the lip.
- 22. (previously presented) The insert according to claim 16, wherein said means for preventing the lining from turning comprise depressions formed in the surface of the wall defining the inside space of the shell, and wherein depressions are formed in the lip.

- 23. (previously presented) The insert according to claim 15, wherein the anterior portion of said shell presents a conical shape.
- 24. (previously presented) The insert according to claim 15, wherein the wall of the receptacle is covered in ceramic.
- 25. (previously presented) The insert according to claim 15, wherein said lining is obtained by an operation of thermocompressing said polymer in said inside space of the shell, followed by a machining operation.
- 26. (previously presented) The insert according to claim 15, wherein said lining is obtained by prior shaping, and wherein it is put into place by being impacted into the shell.
- 27. (currently amended) An acetabular implant of the type comprising a cup for being fastened in the pelvis or a shoulder blade of a patient, and an insert lining the inside of said cup in order to receive a prosthetic head, wherein the insert is of the type according to claim 15.

Docket No. 0512-1306 Appln. No. 10/559,680

- 28. (currently amended) A joint prosthesis of the type comprising an acetabular implant and a prosthetic head, wherein said implant is of the type according to claim 27.
- 29. (new) The insert according to claim 15, wherein said stud is disposed centrally of the shell.
- 30. (new) The insert according to claim 15, wherein said stud is formed integrally with said shell.